



Dentale DR Sensor Newlife Digisens HD



DIGISENS HD

Intraoral Sensor

simplify your work



Bijzondere kenmerken :

- **Beschikbaar in Size 1 en Size 2**
- **CSI Scintillator**
- **Veterinaire software**
- **Dicom Database, en dicom in en out**
- **18µm Pixel size**
- **Gebruiksvriendelijk**
- Lage onderhoudskost en betrouwbaar
- Mobiel inzetbaar
- Onderhoud en **Service door Verachttert Digital**

X-Ray Verachttert Digital nv

Bisschoppenhoflaan 662
2100 Deurne

Telefoon: 03/239.05.79

Fax: 03/218.50.61

E-mail: info@xrayverachttert.be

www.xrayverachttert.be

DIGISENS HD Discover the advantages of our HD sensor

Intraoral Sensor



DIGISENS HD - Intraoral Sensor

The best CMOS technology with an ergonomic design able to adapt easily the anatomy of the oral cavity. DIGISENS HD is an innovative, flexible, very resistant sensor able to produce high quality images.

DIGISENS HD is Immediately Operative

- Easy to install, handle and transport
- It produces high quality **281/p** images in real time.
- Images can be stored in your PC, saving space and time.
- Our Imaging Software can easily manage images stored.

DIGISENS HD Advantages

Our Intraoral sensor produces perfect, high quality images with excellent resolution (**281/p**) without the use of traditional films, no waiting and with very short exposure time. Images are directly sent to your screen.

Our Imaging Software is a dynamic and intuitive system. It guides the user through its practical content by rapidly highlighting its essential functions.

DIGISENS HD in 2 sizes

- Size 1 - Active area of 30 x 20 mm
- Size 2 - Active area of 38 x 26 mm



Size 1 - 30 x 20 mm



Size 2 - 38 x 26 mm

Specifications			
Parameter	Unit	Size 1	Size 2
Sensor Type	-	CMOS Photodiode Array	
X-ray convertor	-	FOS (FOP + CsI)	
Dimensions (W x L x H)	mm	25.4 x 36.3 x 4.8	31.3 x 42.9 x 4.8
Weight	gr	Less than 100	
Pixel Size	µm	18	
Active Area	mm	20.00 x 30.01	25.95 x 37.96
Effective Area*	mm	19.80 x 29.80	25.77 x 37.78
Number of Active Pixels	pixels	1110 x 1666	1442 x 1998
Number of Effective Pixels	pixels	1100 x 1656	1432 x 1988
Data output	-	USB 2.0	
USB cable length	m	Less than 2.7	
Electrical rating		DC 5V. 500 mA	
Operation mode		Global shutter	
Protection against water		IP68	

* X-Ray sensitive area

Recommended operating conditions		
Parameter	Unit	Size 1 size 2
Operating temperature	°C	+10 to +30
Operating humidity	%	30 to 80
Storage temperature	°C	-20 to +60
Storage humidity	%	10 to 80

Sensor performance specifications			
Parameter	Unit	Size 1	Size 2
SNR	dB	≥ 35	≥ 35
Sensitivity ¹	ADU/µGy ²	5,0 to 8,0	5,0 to 8,0
Resolution ³	3lp/mm	≥ 50	≥ 50
	6lp/mm	≥ 25	≥ 25
	8lp/mm	≥ 15	≥ 15
Noise ⁴	ADU	≤ 2.0	≤ 2.0
A/D	Bits	12	12
Energy Range ⁵	kVp	60 ~ 70	60 ~ 70

Voor verdere informatie, neem contact met :
X-Ray Verachttert Digital nv

Bisschoppenhoflaan 662
 2100 Deurne - Belgie
www.xrayverachttert.be

Telefoon: +32 (0)3 239 05 79
 Fax: +32 (0)3 218 50 61
 E-mail: info@xrayverachttert.be